

CRIMP TYPE LATCH SOCKET




2420 SERIES. 2.50mm(0.098"). Socket

Features

- Available in 2 through 15 circuits
- Mates with 2421 and 2422 headers
- Material: Nylon 6/6 UL94V-0
- Accepts 2453 series crimp terminals
- Polarised with locking ribs
- Low profile

Dimensional Information



Ordering and Dimensional Information

Circuit Size	Part Number	Dimensions		
		A	B	C
02	2420-2021	2,50(0,098)	7,00 (0,276)	5,30 (0,209)
03	2420-2031	5,00(0,197)	9,50 (0,374)	7,80 (0,307)
04	2420-2041	7,50(0,295)	12,00 (0,472)	10,30 (0,406)
05	2420-2051	10,00(0,394)	14,50 (0,571)	12,80 (0,504)
06	2420-2061	12,50(0,492)	17,00 (0,669)	15,30 (0,602)
07	2420-2071	15,00(0,591)	19,50 (0,768)	17,80 (0,701)
08	2420-2081	17,50(0,689)	22,00 (0,866)	20,30 (0,799)
09	2420-2091	20,00(0,787)	24,50 (0,965)	22,80 (0,898)
10	2420-2101	22,50(0,886)	27,00 (1,063)	25,30 (0,996)
11	2420-2111	25,00(0,984)	29,50 (1,161)	27,80 (1,094)
12	2420-2121	27,50(1,083)	32,00 (1,260)	30,30 (1,193)
13	2420-2131	30,00(1,181)	34,50 (1,358)	32,80 (1,291)
14	2420-2141	32,50(1,280)	37,00 (1,457)	35,30 (1,390)
15	2420-2151	35,00(1,378)	39,50 (1,555)	37,80 (1,488)