

WIRE TELEPHONE JACKS FCC-68



6825 to 6841 SERIES.. With Different Terminations.

Electrical Features

- Maximum Voltage: 125 V DC
- Current Rating: 1.5 A for contact
- Insulation Resistance: 10 MΩ – 500V AC
- Contact Resistance: 20 mΩ max.
- Dielectric Withstanding: 1000 VAC for one minute

Mechanical Features

- Conexion Force
 - 2 contacts: 350 gr.
 - 4 contacts: 500 gr.
 - 6 contacts: 750 gr.
 - 8 contacts: 900 gr.
- Retention Force:
 - 7.70 Kg between Plug and Jack
 - 2.27 Kg. Between Phosphor Bronze wire and cable

Special Options

- Cable Length
- Optional Ends
- Consult Options With the Sales Office

Version	Model	Series
6/4	INSERT 625	6825
4/4	INSERT 616	6826
4/4	616 T	6827
4/4	616 W	6828
4/4	616 L	6829
6/6	623 K	6830
4/4	616 B	6831
4/4	616 C	6832

Version	Model	Series
4/4	616 D	6833
4/4	616 E	6834
4/4	616 M	6835
4/4	616 p	6836
6/6	645 O	6837
6/6	623 D	6838
6/6	623 P	6839
6/6	623 T	6840
8/8	641 D	6841

6825 SERIES.. 6/6 Jack INSERT 625 Model.

Dimensional Information

