

SOCKETS PLUGGABLE LIGHT PIPE SPRING



BC0225LP* SERIES. 3.50 mm. (0.138"). With LIGHT PIPE.

General Features

- Available in 2 through 14 circuits
- Ultra-thin housing design and easy pluggable style
- Mates with 3.50 mm. pitch plugs pluggable terminal blocks BC02250 series with PIPE LIGHT
- Full polarised. Low profile (7.50 mm. with Pipe Light)
- Meet UL 1059 requirements

Materials

- Insulator: PBT UL 94 V-0.
- Contact: Cooper alloy tin plated
- Operating temperature: -40°C to +115°C
- RoHS compliant


Dimension Information

Electrical Features

- Voltage rating: 300V UL / 630V IEC
- Rated current: 8 A UL / 15 A IEC
- Contact resistance: < 20 mΩ
- Rated surge voltage: 4000 V
- Insulation resistance: >500 MΩ


Mechanical features

- Durability: 25 cycles




P/N.: **BC0225-11XX**

XX= N° CONTACTS




P/N.: **BC0225-21XX**

XX= N° CONTACTS




P/N.: **BC0225-31XX**

XX= N° CONTACTS




P/N.: **BC0225-12XX**

XX= N° CONTACTS



P/N.: **BC0225-22XX**

XX= N° CONTACTS



P/N.: **BC0225-32XX**

XX= N° CONTACTS