

WIRE TELEPHONE JACKS FCC-68



6825 to 6841 SERIES.. With Different Terminations.

Electrical Features

- Maximum Voltage: 125 V DC
- Current Rating: 1.5 A for contact
- Insulation Resistance: 10 MΩ – 500V AC
- Contact Resistance: 20 mΩ max.
- Dielectric Withstanding: 1000 VAC for one minute

Mechanical Features

- Conexion Force
 - 2 contacts: 350 gr.
 - 4 contacts: 500 gr.
 - 6 contacts: 750 gr.
 - 8 contacts: 900 gr.
- Retention Force:
 - 7.70 Kg between Plug and Jack
 - 2.27 Kg. Between Phosphor Bronze wire and cable

Special Options

- Cable Length
- Optional Ends
- Consult Options With the Sales Office

| Version | Model | Series |
|---------|------------|--------|
| 6/4 | INSERT 625 | 6825 |
| 4/4 | INSERT 616 | 6826 |
| 4/4 | 616 T | 6827 |
| 4/4 | 616 W | 6828 |
| 4/4 | 616 L | 6829 |
| 6/6 | 623 K | 6830 |
| 4/4 | 616 B | 6831 |
| 4/4 | 616 C | 6832 |

| Version | Model | Series |
|---------|-------|--------|
| 4/4 | 616 D | 6833 |
| 4/4 | 616 E | 6834 |
| 4/4 | 616 M | 6835 |
| 4/4 | 616 p | 6836 |
| 6/6 | 645 O | 6837 |
| 6/6 | 623 D | 6838 |
| 6/6 | 623 P | 6839 |
| 6/6 | 623 T | 6840 |
| 8/8 | 641 D | 6841 |

6825 SERIES.. 6/6 Jack INSERT 625 Model.

Dimensional Information

