

# 3.96mm DUAL ROW EDGE CARD CONNECTOR



## 4200 SERIES. 3.96mm(0.156"). For Cable Solder.

### Features

- Available in 5/10, 6/12, 8/16, 10/20, 12/24, 15/30, 18/36, 20/40, 22/44, 24/48, 28/56, 30/60, 36/72 & 43/86 circuits.
- Insulator Material: P.B.T. UL 94V-0
- Contact Material: Brass
- Bifurcated anti-lever beam type.
- Accept P.C. Board thickness: 1.40 – 1.60mm
- For easy insertion and extraction to P.C. Board

### Dimensional Information

### Ordering and Dimensional Information

Circuit Size	Part Number	Dimensions				
		A	B	C	D	E
5/10	4200-T051	41.20	34.94	27.40	24.06	15.84
6/12	4200-T061	45.16	38.90	31.36	28.02	19.80
8/16	4200-T081	53.08	46.82	39.28	35.94	27.72
10/20	4200-T101	61.00	54.74	47.20	43.86	35.64
12/24	4200-T121	68.92	62.66	55.12	51.78	43.56
15/30	4200-T151	80.80	74.54	67.00	63.66	55.44
18/36	4200-T181	92.68	86.42	78.88	75.54	67.32
20/40	4200-T201	100.60	94.34	86.80	83.46	75.24
22/44	4200-T221	108.52	102.26	94.72	91.38	83.16
24/48	4200-T241	116.44	110.18	102.26	99.30	91.08
28/56	4200-T281	132.28	126.02	118.48	115.14	106.92
30/60	4200-T301	140.20	133.94	126.40	123.06	114.84
36/72	4200-T361	163.96	157.77	150.16	146.82	138.60
43/86	4200-T431	191.48	185.49	177.88	174.52	166.32

### T = Contact Plating

- T = 3. Gold flash over 50μ" nickel
- T = 5. 15μ" gold over 50μ" nickel

