

SINGLE ROW RIGHT ANGLE PIN HEADER



3988 SERIES. 3.96 mm. (0.156") pitch.



General Features

- Available in 2 through 40 circuits
- Mates with PCB sockets 3.96mm pitch 3970, 3971, 3972, 3915, 3916. Wire housing 3940, 3930, 2631 and 3950 series
- 1.14 mm. square pin tin plated
- With stand-off to minimise flux retention
- Easy breakaway desired circuit size

Materials

- Insulator: High temperature thermoplastic UL 94 V-0
- Contact: brass
- Operating temperature: -40°C to +105°C
- RoHS compliant

Dimensional Information




Electrical Features

- Voltage rating: < 250V
- Current rating: < 5 A
- Contact resistance: < 20 mΩ
- Dielectric withstanding voltage: 600 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Pin retention force to insulator: > 0,50 Kgf
- Durability: 50 cycles



Ordering Information:

3988 - T- XX- 1

1 2 3

1. Connector Series

2. (T) Contact Plating

- T = 2. Tin plated
Recommended Finish

3. (XX) Number of circuits

- Available in 2 through 20 circuits

Dimensions: (In mm.)

A = 3.96 x (XX*-1)

B = 3.96 x (XX*)

* XX (Number of circuits)