

# SINGLE ROW RIGHT ANGLE PIN HEADER



## 5088 SERIES. 5.08 mm (0.200") pitch.



### General Features

- Available in 2 through 20 circuits
- Mates with PCB sockets 5.08 mm pitch 1507, 1508, 1509, 5069, 5070 series and wire housing 5080 and 5081 series
- 1.14 mm. square pin
- With standoff to minimise flux retention

### Materials

- Insulator: Glass filled Polyester UL 94 V-0
- Contact: brass
- Operating temperature: -40°C to +85°C
- RoHS compliant

### Dimensional Information




### Electrical Features

- Voltage rating: < 250V
- Current rating: < 5 A
- Contact resistance: < 20 mΩ
- Dielectric withstanding voltage: 1500 V AC/minute
- Insulation resistance: >1000 MΩ

### Mechanical Features

- Pin retention force to insulator: > 0,50 Kg
- Durability: 25 cycles



### Ordering Information:

**5088 - T- XX- 1**

1 2 3

#### 1. Connector Series

#### 2. (T) Contact Plating

- T = 2. Tin plated  
Recommended Finish

#### 3. (XX) Number of circuits

- Available in 2 through 20 circuits

Dimensions: (In mm.)

A = 5.08 x (XX\*-1)

B = 5.08 x (XX\*)

\* XX (Number of circuits)