

General Features

- ## Electrical Features

- ## Materials

- ## Mechanical Features

- Insertion force per contact: < 0.30 Kg
- Withdrawal force per contact: < 0.015 Kg
- Durability: 500 Cycles

Dimension Information

Circuits	Part Number	Dimensions			
		A	B	C	D
15	8085 – T15C	16.33 [0.643]	24.99 [0.984]	30.81 [1.213]	2.29 [0.090]
26	8085 – T26C	24.66 [0.971]	33.32 [1.312]	39.14 [1.541]	2.29 [0.090]
44	8085 – T44C	38.38 [1.511]	47.04 [1.852]	53.04 [2.088]	2.29 [0.090]
62	8085 – T62C	54.84 [2.159]	63.50 [2.500]	69.32 [2.729]	2.41 [0.095]

T = Contact Plating

- T = **3.** Gold flash over 50μ" nickel.
- T = **4.** 10μ" gold over 50μ" nickel
- T = **5.** 15μ" gold over 50μ" nickel
- T = **6.** 30μ" gold over 50μ" nickel

C = Hardware Options

- C = 1. Riveted ground hooks pre-loaded
#4.40 UNC Hex screws (standard)
- C = 0. Riveted ground hooks with
#4.40 UNC open

