

TRIPLE ROW VERTICAL SOCKET



8362 SERIES. 1.27 mm. (0.050") pitch. Machined contact.



General Features

- Available in 6 through 120 circuits
- Mates with Pin headers 1.27mm. pitch 8352, 8355 and 8358 series
- Accept round pin 0.38 to 0.50 mm.
- Low profile 4.00 mm. high
- Machined contact with different plating




Materials

- Insulator: PPS black + 30% GF UL 94 V-0
- Contact: Clip (3 fingers) in Beryllium copper
- Sleeve: Brass
- Operating temperature. -40°C to +105°C
- RoHS compliant

Dimension Information



Circuits Configuration



DIMENSIONS:

$$A = 1.27 \left(\frac{XX}{3} - 1 \right) \quad B = 1.27 \left(\frac{XX}{2} \right) + 0.41$$


XX = Number of circuits

Electrical Features

- Voltage rating: < 100V
- Current rating: < 1 A
- Contact resistance: < 10 mΩ
- Dielectric withstanding Voltage: 1000 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Insertion force per pin: < 0.25 Kgf (round pin 0.41 mm)
- Withdrawal force per pin: > 0.03 Kgf (round pin 0.41 mm)
- Durability: 500 Cycles



Ordering Information:

8362 - T- XX- S
 1 2 3 4

1. Connector Series

2. (T) Contact Plating

- T = 13. Selec. gold flash over 30-50μ" Ni overall Recommended Finish
- T = 15. 15μ" selec. gold over 30-50μ" Ni overall
- T = 16. 30μ" selec. gold over 30-50μ" Ni overall

3. (XX) Number of circuits

- Available in 6 through 120 circuits

4. S = Circuits Configuration

- S = 1. 3 rows of contacts: A+B+C
- S = 2. 2 rows of contacts: A+C