SINGLE ROW VERTICAL PIN HEADER



8390 SERIES. 2.54 mm. (0.100") pitch. Machined contact.


General Features


- Available in 2 through 40 circuits
- 0.60 round pin in contact area
- With different plating options

Materials

- Insulator: PPS black + 30% GF UL 94 V-0
- Contact: Brass
- Operating temperature. -40°C to +105°C
- RoHS compliant

Dimension Information






Flectrical Features

- Voltage rating: < 250V
- Current rating: < 3 A
- Contact resistance: < 10 mΩ
- Dielectric withstanding Voltage: 1000 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Pin retention force to insulator: > 0.80 Kgf
- Durability: 500 Cycles



Ordering Information:

- 1. Connector Series
- 2. (T) Contact Plating
- T = 3. gold flash over 30-50µ" Ni overall Recommended Finish
- T = **15**. 15µ" selec. gold over 30-50µ" Ni
- T = 16. 30μ" selec. gold over 30-50μ" Ni overall
- 3. (XX) Number of circuits
- Available in 2 through 40 circuits

Dimensions: (In mm.)

 $\mathbf{A} = 2.54 \text{ x (XX*-1)}$ $\mathbf{B} = 2.54 \text{ x (XX*)} + 0.41$

* XX (Number of circuits)

A-XX FULL LINE CATALOGUE