

PLUG FOR PLUGGABLE SPRING CLAMP



BC01343* SERIES. 7.50 mm. (0.295") pitch. For wire spring Type

General Features

- Available in 2 through 24 circuits
- Mates with 7.50 mm. pitch headers (Socket) pluggable terminal blocks
- Front wire entry. Full polarised
- Meet UL and IEC standards

Materials

- Insulator: PA66 UL 94 V-0
- Contact: phosphor bronze tin plated
- Spring: High-strength steel alloys zinc plated
- Operating temperature: -40°C to +105°C
- RoHS compliant

Dimension Information

Electrical Features

- Voltage rating: 300V UL; 450V IEC;
- Rated current: 15 A UL / 12 A IEC
- Contact resistance: < 20 mΩ
- Rated surge voltage: 1600V UL / 6000 V IEC
- Insulation resistance: >500 MΩ

Mechanical features

- Wire strip length: 10.00 mm.
- Conductor cross-section: AWG 26-14
- Durability: 25 cycles

<p>P/N: BC013431-XX XX= N° CONTACTS</p>	<p>*24 A IEC / 1000 V IEC P/N: BC013432-XX XX= N° CONTACTS</p>	<p>P/N: BC013433-XX XX= N° CONTACTS</p>
<p>*24 A IEC / 1000 V IEC P/N: BC013434-XX XX= N° CONTACTS</p>		