

PLUG/HEADERS FOR PLUGGABLE T. BLOCK



BC01471*, BC01481* SERIES. 5.00 mm. (0.197") pitch. PCB Type Spring Clamp.

General Features

- Available in 2 through 24 circuits
- Full polarised
- Top and side entry
- Meet UL and IEC standards

Materials

- Insulator: PA66 UL 94 V-0
- Contact: Electrolytic copper tin plated
- Operating temperature: -40°C to +105°C
- RoHS compliant

Dimension Information

Electrical Features

- Voltage rating: 300 V UL; 6000 V IEC;
- Rated current: 15 A UL / 24 A IEC
- Contact resistance: < 20 mΩ
- Rated surge voltage: 1600V UL / 4000 V IEC
- Insulation resistance: >500 MΩ

Mechanical features

- Wire strip length: 8.00 to 9.00 mm.
- Conductor cross-section: AWG 26-12
- Durability: 25 cycles

<p>P/N: BC014711-XX XX= N° CONTACTS</p>	<p>P/N: BC014811-XX XX= N° CONTACTS</p>	<p>P/N: BC014813-XX XX= N° CONTACTS</p>
<p>P/N: BC014712-XX XX= N° CONTACTS</p>	<p>P/N: BC014812-XX XX= N° CONTACTS</p>	<p>P/N: BC014814-XX XX= N° CONTACTS</p>