PLUG/HEADERS FOR PLUGGABLE T. BLOCK

BC01473*, BC01483* SERIES. 7.50 mm. (0.295") pitch. PCB Type Spring Clamp.

General Features

- Available in 2 through 12 circuits
- Full polarised
- Top and side entry
- Meet UL and IEC standards

Electrical Features

- Voltage rating: 300 V UL; 1000 V IEC;
- Rated current: 15 A UL / 24 A IEC
- Contact resistance: < 20 mΩ
- Rated surge voltage: 1600V UL / 6000 V IEC
- Insulation resistance: >500 MΩ

Materials

- Insulator: PA66 UL 94 V-0
- Contact: Electrolytic copper tin plated
- Operating temperature: -40ºC to +105ºC
- RoHS compliant

Mechanical features

- Wire strip length: 8.00 to 9.00 mm.
- Conductor cross-section: AWG 28-12
- Durability: 25 cycles

Dimension Information



P/N: **BC014731-XX**

XX= Nº CONTACTS



P/N: **BC014831-XX**

XX= Nº CONTACTS



P/N: **BC014833-XX**

XX= Nº CONTACTS



P/N: **BC014732-XX**

XX= Nº CONTACTS



P/N: **BC014832-XX**

XX= Nº CONTACTS



P/N: **BC014834-XX**

XX= Nº CONTACTS